



Demolition Derby RULES

- 4 Cylinders Division must have 105 inch or under wheel base
- Full Size Division must have 105 inch or more wheel base, and may have 6 or 8 cylinders
- No Hearses or Ambulances will be allowed
- No Valve Stem Protectors
- Stock tires must be used – no hard rubber tires or snow tires – air only in tires; no liquids
- Water Only in Radiators – Gas engines only no Diesel Engines
- Hoods and trunk lids must be tied down with rope
- 12 inch hold must be cut into hood and trunk lid in case of fire
- Fuel Tanks may be replaced with Fuel Cells or Smaller Tanks. All tanks must be securely fastened
- Electric fuel pumps must have a well marked fuel shut off switch
- NO MORE THAN 5 Gallons of Gas only in fuel tanks
- Batteries may be moved to inside of vehicle, but must be covered and bolted down
- All glass must be removed except for windshields. If removed, windshields must be replaced with screen or lexan
- All Chrome, Hub Caps, Antennas, Wheel Weights, and exterior plastic must be removed
- Seat belts must be functional and worn at all times
- Broken seats will result in immediate disqualification
- Foam Padding in Drivers Door is mandatory
- NO DRIVER'S DOOR HITS WILL BE TOLERATED
- Doors must be chained or welded – Maximum 1/8th inch Steel plate may be used on outside of door
- Helmets and goggles, or Face Shields, must be worn with chin straps fastened at all times
- No offensive, lewd or vulgar lettering or pictures allowed.