

Demolition Derby RULES

- 4 Cylinders Division must have 105 inch or under wheel base.
- Full Size Division must have 105 inch or more wheel base, and may have 6 or 8 cylinders.
- No Hearses or Ambulances will be allowed.
- No Valve Stem Protectors.
- Stock tires must be used – no hard rubber tires or snow tires – air only in tires; no liquids.
- Water Only in Radiators – Gas engines only no Diesel Engines.
- Hoods and trunk lids must be tied down with rope.
- Trunk lids can not be removed from the car.
- 12 inch hold must be cut into hood and trunk lid in case of fire.
- Fuel Tanks may be replaced with Fuel Cells or Smaller Tanks. All tanks must be securely fastened.
- Electric fuel pumps must have a well marked fuel shut off switch.
- NO MORE THAN 5 Gallons of Gas only in fuel tanks.
- Batteries may be moved to inside of vehicle, but must be covered and bolted down.
- Battery cables that travel through the windshield must go through the lower right hand corner and be taped over.
- All glass must be removed except for windshields. If removed, windshields must be replaced with screen or lexan.
- All Chrome, Hub Caps, Antennas, Wheel Weights, and exterior plastic must be removed from vehicle.
- Plastic bumper covers must be removed.
- Seat belts must be functional and worn at all times.
- Broken seats will result in immediate disqualification.
- Foam Padding in Drivers Door is mandatory!
- **NO DRIVER'S DOOR HITS WILL BE TOLERATED!**
- Doors must be chained or welded – Maximum 1/8th inch Steel plate may be used on outside of door.
- Helmets and goggles, or Face Shields, must be worn with chin straps fastened at all times.
- No offensive, lewd or vulgar lettering or pictures allowed.

Notice: All components must stay in there stock location except the battery and fuel tank. If found in violation you will be able to participate in the derby if cleared by the techs, but will only be eligible for half of the pay out value if you place.